

# Miller Cross-Arm Chain Anchorage Connector

Model: 440/6FT

## Description

The 6-ft. (1.8m) Chain Anchor provides a single user with an easy-to-install, temporary anchorage connector. It easily wraps around I-beams or other structures. This product safely wraps around corners and sharp edges and is ideal to use in environments where chemical, heat or welding splatter may occur.

## Materials

**Chain:** 9/32" (7.1mm) Grade 80 Steel  
**Long Links:** 1/2" (12.7mm) Alloy Steel  
**Connecting Links:** 9/32" (7.1mm) Grade 80 Steel

\*All hardware meets ASTM (50) fifty-hour salt spray test requirements

## Technical

### Maximum Working

### Load Capacity:

400 lbs (181.4 kg)

### Chain:

5,000 lbs (22 kN) minimum tensile strength

### Links:

5,000 lbs (22 kN) minimum tensile strength

### Length:

6 ft (1.8m)



## Certification

OSHA 1926.502, OSHA 1910.66, ANSI A10.32 and ANSI Z359.1-2007

# MILLER®

by Honeywell

Toll Free 800.873.5242 (press 4) • [hsptechsupport@honeywell.com](mailto:hsptechsupport@honeywell.com) • [www.millerfallprotection.com](http://www.millerfallprotection.com)

**WARNING!** THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.