

## Release Notes

Product Name: Honeywell Safety Suite

Device Configurator Version: V2.1.3

Operating System: Windows® 7

(x86 and x64), Windows 10 (x64)

Release Date: February 19, 2019

---

### WHAT'S NEW

**This release supports the following features:**

#### 1. Reporting

This release adds additional reports for multi-device event log and calibration/bump-test reporting. Users can also create a custom header with logo to personalize their reports.

#### 2. Custom Fields

Users can now define up to five custom fields to store implementation-specific information about their devices.

#### 3. Data Download

Users will now be able to initiate data download from multiple docking stations simultaneously. In addition, users can define a schedule to download data automatically from the connected MicroDock IIs and IntelliDoXs.

#### 4. MicroDock II Configuration File

This update allows users to update the MicroDock II configuration file directly, eliminating the need for the MicroDock II to be physically connected to the computer with the software.

---

### INSTALLATION AND UPDATE NOTES

#### Before installation:

Close all other programs.

#### Installation:

1. Download the software from the Honeywell Safety Suite [website](#).
2. Launch the installer by double-clicking the installation file.
3. Follow the instructions for installation. The initial installation can take between 15 and 20 minutes.
4. Once the software is successfully installed, an “Installed Successfully” message is displayed. Click the “FINISH” button to exit the installation program or click the “LAUNCH APPLICATION” button to exit the installation program and launch Honeywell Safety Suite Device Configurator.

## SUPPORTED INSTRUMENTS AND FIRMWARE

### BW PRODUCTS

No.	Instrument	Firmware Version
1	IntelliDoX	10.100
2	MicroDock II	N/A
3	BW Clip & BW Clip Real Time	2.101
4	BW Clip4	1.3.4
5	BW Max XT II	12.000
6	BW MicroClip XL & BW MicroClip XT	50B
7	BW Quattro	4.000
8	BW Solo	1.020
9	BW Ultra	1.001
10	GasAlertMicro 5	N/A

### RAE SYSTEM PRODUCTS

No.	Instrument	Firmware Version
1	AutoRAE 2 Controller	1.34A
2	AutoRAE Cradle for Handheld PID Monitor	1.34
3	AutoRAE 2 Cradle for MicroRAE	1.34
4	AutoRAE 2 Cradle for MultiRAE	1.34
5	AutoRAE 2 Cradle for QRAE 3	1.34
6	AutoRAE 2 Cradle for ToxiRAE Pro	1.34
7	AreaRAE Plus & AreaRAE Pro	1.08
8	MicroRAE	1.10A
9	MiniRAE 3000 & MiniRAE Lite	2.16
10	MultiRAE, MultiRAE Lite, & MultiRAE Pro	1.40C
11	ppbRAE 3000	2.16
12	QRAE 3	2.14
13	ToxiRAE Pro, ToxiRAE Pro CO2, ToxiRAE Pro LEL, ToxiRAE Pro PID	1.80
14	UltraRAE 3000	2.16

## KNOWN ISSUES AND WORKAROUNDS

No.	ISSUE	WORKAROUND
1	After changing the short date format, the new date format is not reflected in the software.	Close and re-launch the application, or logout and re-login to view the date format change.
2	After changing the machine's time zone, the Last Communication Time is not updated on the Inventory page.	Click the Refresh button on the Inventory page to update the Communication Time to reflect the new time zone.

## PREVIOUS VERSIONS

### Honeywell Safety Suite Device Configurator v2.0.0

**What's New** This release supports the following features:

#### 1. Fleet Manager II Data Migration

Safety Suite Device Configurator now supports data migration from Fleet Manager II for all the supported instruments. In addition, it supports data migration for GasAlert Extreme. However, existing Fleet Manager II instances should be upgraded to the latest version before initiating data migration.

#### 2. ProRAE Studio II Data Migration

Safety Suite Device Configurator now supports data migration from ProRAE Studio II for all the supported instruments. However, existing ProRAE Studio II instances should be upgraded to the latest version before initiating data migration.

#### 3. IQ Management Software Suite Data Migration

Safety Suite Device Configurator now supports data migration from IQ Management Software Suite for ToxiPro.

#### 4. IntelliDoX USB Support

Safety Suite Device Configurator now supports device configuration and data download through IntelliDoX USB connector for BW Clip, BW Clip Real Time, BW MicroClip XL, and BW MicroClip X3.

#### 5. RAE Travel Charger Support

Safety Suite Device Configurator now supports device connectivity through RAE Travel Charger.

---

### Honeywell Safety Suite Device Configurator v1.1.0

**What's New** This release supports the following features:

#### 1. MicroDock II Support Honeywell

Safety Suite Device Configurator now supports instrument connectivity through MicroDock II in addition to IntelliDoX for BW instruments.

#### 2. Legacy Data Download

Data download for IntelliDoX, MicroDock II, and AutoRAE 2 now provides the ability to download all the legacy data from the docking station.

---

### Honeywell Safety Suite Device Configurator v1.0.0

**What's New** This release supports the following features:

#### 1. Instrument Connectivity

Safety Suite Device Configurator currently supports instrument connectivity through IntelliDoX and AutoRAE 2 for BW and RAE Systems instruments respectively. For IntelliDoX, data transfer using the USB data download will be provided in future releases.

#### 2. Device Configuration

Device Configuration is supported for IntelliDoX and AutoRAE 2 as well as the supported instruments.

---

### 3. Device Templates

Device templates for RAE Systems instruments can be used to define instrument settings once to apply across multiple instruments.

### 4. Firmware Management

Perform device firmware updates using on-screen notifications for obsolete firmware and one-click firmware updates. Manual firmware updating is also supported in case the software is not connected to the Internet.

### 5. Worker Device Assignment

Easily track which workers are using which instruments by managing instrument worker assignment through the software.

### 6. Device History

Device History is used to report on device events, logs, calibration, and bump test results. Drill-down views extract the pertinent data for reviewing selected details. Data can be exported in csv (comma-separated value) format for further analysis in programs such as Microsoft Excel.

### 7. Reporting

Key reports for instrument events, calibration, and bump tests can be generated in PDF format.

### 8. User Management

Access to the system is safeguarded through user accounts. Role-based function access ensures that only the appropriate individuals can access the specified functionality.

#### Find out more

For more information visit:

<https://www.honeywellaidc.com/solutions/connected-worker/safety-suite>

#### Europe, Middle East, Africa

[gasdetection@honeywell.com](mailto:gasdetection@honeywell.com)

#### Americas

[detectgas@honeywell.com](mailto:detectgas@honeywell.com)

#### Asia Pacific

[analytics.ap@honeywell.com](mailto:analytics.ap@honeywell.com)

#### Technical Support

[support.safetysuite@honeywell.com](mailto:support.safetysuite@honeywell.com)

1-833-556-3515

Microsoft and Windows are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners.

Note: Due to ongoing research and product improvement, specifications are subject to change without notice.

Safety Suite Device Configurator Release Notes | Rev B | 02/19  
© 2019 Honeywell International Inc.

**Honeywell**