

Midas[®] SENSOR CARTRIDGE SPECIFICATIONS

Carbon Dioxide (CO₂) MIDAS-S-CO₂, MIDAS-E-CO₂



Gas Measured	Carbon Dioxide (CO ₂)
Cartridge Part Number	MIDAS-S-CO ₂ 1 year standard warranty MIDAS-E-CO ₂ 2 year extended warranty
Sensor Technology	3 electrode electrochemical cell
Measuring Range (ppm)	CO ₂ 0 – 2% v/v
Minimum Alarm 1 Set Point	2500ppm
Repeatability	< ± 0.06% v/v
Linearity	< ± 15% of measured value
Response Time t_{92.5}	< 70 seconds
Sensor Cartridge Life Expectancy	≥ 24 months under typical application conditions
Operating Temperature	0°C to + 40°C (32°F to 104°F)
Effect of Temperature	< 0.0039% vol / °C (0°C to 20°C) < ± 0.0053% vol / °C (20°C to 40°C) < 1.9% of measured value / °C (0°C to 20°C) < ± 0.9% of measured value / °C (20°C to 40°C)
Operating Humidity (continuous)	
Effect of Humidity	15 – 95% rH
Zero	No effect
Sensitivity	< ± 1% of measured value / % rH
Operating Pressure	90 – 110kPa
Effect of Position	No effect in typical application
Long Term Drift	
Zero	< +0.3% vol / year
Sensitivity	< 30% of measured value / 1 year
Calibration Gas	Carbon Dioxide (CO ₂)
Challenge Gas (Bump Test)	Carbon Dioxide (CO ₂)
Warm Up Time	< 20 minutes
Storage Temperature	+5°C to +25°C (+41°F to +77°F)

The sensor data listed is based on ideal test environment; observed performance may vary based on the actual monitoring system and the sampling conditions employed

Cross Sensitivities

Each Midas[®] sensor is potentially cross sensitive to other gases and this may cause a gas reading when exposed to other gases than those originally designated. The table below presents typical readings that will be observed when a new sensor cartridge is exposed to the cross sensitive gas (or a mixture of gases containing the cross sensitive species).

Gas / Vapor	Chemical Formula	Concentration applied (ppm)	Reading (ppm CO ₂)
Carbon Monoxide	CO	500	< 0.05
Chlorine	Cl ₂	2	< 0.05
Hydrogen	H ₂	1000	< 0.05
Hydrogen Sulphide	H ₂ S	75	< 0.05
Methane	CH ₄	20000	< 0.05
Nitrogen Dioxide	NO ₂	50	< 0.05
Sulphur Dioxide	SO ₂	50	< 0.05
Methanol	CH ₃ OH	1000	< 0.05

Find out more

www.honeywellanalytics.com

Toll-free: 800.538.0363

Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.