

## 301EMRP-20 SPECIFICATIONS

### Controller Remote Panel



General Specification													
<b>Use</b>	Remote Panel for the 301EM-20 offers four relay outputs and visual indication of the gas concentration outside or inside a room.												
<b>Standard Outputs</b>	4 DPDT relays 3 Outputs at 24 VDC @ 250mA each												
<b>Audible Alarm</b>	65dBA @ 3 ft. (1 m)												
<b>Display</b>	Backlit LCD												
<b>Visual Indicators</b>	<table border="1"> <tbody> <tr> <td>Normal operation</td> <td>Green LED</td> </tr> <tr> <td>Alarm Level 1</td> <td>Red LED</td> </tr> <tr> <td>Alarm Level 2</td> <td>Red LED</td> </tr> <tr> <td>Alarm Level 3</td> <td>Red LED</td> </tr> <tr> <td>Fault/service alarm</td> <td>Yellow LED</td> </tr> <tr> <td>Tx (When transmitting to the 301EMRP)</td> <td>Amber LED</td> </tr> </tbody> </table>	Normal operation	Green LED	Alarm Level 1	Red LED	Alarm Level 2	Red LED	Alarm Level 3	Red LED	Fault/service alarm	Yellow LED	Tx (When transmitting to the 301EMRP)	Amber LED
Normal operation	Green LED												
Alarm Level 1	Red LED												
Alarm Level 2	Red LED												
Alarm Level 3	Red LED												
Fault/service alarm	Yellow LED												
Tx (When transmitting to the 301EMRP)	Amber LED												
<b>Maximum distance between 301EM-20 and 301EMRP-20</b>	1,000 ft. (from 301EM-20 to the last 301EMRP-20)												
<b>Relay Output Rating</b>	5A, 30 VDC or 250 VAC (resistive load)												
<b>Power Requirement</b>	22-27 VAC, 50 or 60 Hz, 29-38 VDC, 2.0A max @ 24 VDC												
<b>Operating Environment</b>	Indoor use												
<b>Operating Temperature Range</b>	32° to 100°F (0° to 40°C)												
<b>Operating Humidity Range</b>	0 to 95% RH (non-condensing)												
<b>Operating Altitude</b>	Up to 9,843 ft. (3,000 m)												
<b>Enclosure</b>	ABS - Polycarbonate												
<b>Transmitter Size</b>	8 (H) x 11 (W) x 2.8 (D) in. (20.3 x 28 x 7 cm)												
<b>Transmitter Weight</b>	2.26 lbs. (1.02 kg)												
Ratings and Certification													
	UL 1244 - Fourth edition, October 2000												
	CSA C22.2 No 205-M1983 (R1999)												

#### Find out more

[www.honeywellanalytics.com](http://www.honeywellanalytics.com)

Toll free: 1 800 563 2967

#### Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.